

Fire-resistant document and valuable safes Model "LEIPZIG", VdS class I, S 120 P



Illustration: Article 71403

Insurance protection:
Private from up to 65,000 €, commercial up to 20,000 €.
Burglary protection according to EN 1143-1, VdS class I.
Fire resistance according to EN 1047-1, S 120 P.
Body and door in multi-wall design.
Door thickness 134 mm, with all-sided bolt locking system.
Special fillings and sealing systems protect the content of the safe against fire and firefighting water.
Serial design prepared for floor anchoring.
Locking by means of a double bit security lock, lock class I (incl. 2 keys).

Colour: RAL 7035 grey

Article	Model	Outer dimensions in mm HxWxD	Inner dimensions in mm HxWxD	Door passage dimensions in mm	weight kg	shelves
71401	LEIPZIG	1375x800x570	1115x660x334	1070x570	520	2
71402	LEIPZIG	1575x800x570	1315x660x334	1270x570	600	3
71403	LEIPZIG	1775x800x570	1515x660x334	1470x570	650	3
71420	Mechanical number combination lock instead of double bit lock					
71421	Electronic lock with revision instead of double bit lock					
71422	Electronic lock without revision instead of double bit lock					
71423	Interior safe 240 mm high, with cylinder lock, for articles 71400 - 71403					
71424	Interior safe 400 mm high, with partition wall and with cylinder lock, for article 71404					
71425	Shelf, extendable, on telescopic rails, for articles 71400 - 71403					
71426	Shelf, extendable, on telescopic rails, for article 71404					
71427	Extendable suspension files on telescopic rails, for articles 71400 - 71403					
71428	Extendable suspension files on telescopic rails, for article 71404					
71430	Diskette insert, AMH 680 x W 560 x D 348, IMH 450 x W 355 x D 144, 21 ltrs., approx. 100 CD-R, for articles 71400 - 71404					
71450	Accessories acc. to VDMA requirements, anchor bolt, threaded rod, driving tool					